



B2337

6" UNIVERSAL KNIFE GRINDER

User Manual



SAFETY INSTRUCTIONS

- 1.Read the owners manual carefully before using.
- 2.Keep guards in place and keep unnecessary people away.
- 3.Keep work area clean.Don't use in dangerous environment.
- 4.Make workshop kid-proof . Use padlocks , master switches or by removing starter keys . Remove adjusting keys and wrenches before turning it on.
- 5.Don't force a tool or attachment to do a job for which it was not designed.
- 6.Wear proper apparel and always use safety glasses . Wear protective hair covering to contain long hair.
- 7.Use clamps or a vise to hold work when practical . It's safer than using your hand and it frees both hands to operate tool. Disconnect tools before servicing.
- 8.Make sure switch is in off position before plugging in keep tools sharp and clean for best and safe performance. Follow instructions for lubricating and changing accessories.Carefully check damaged parts.
- 9.Never leave tool running unattended,turn power off.

SPECIFICATIONS

Maximum Knife Length:24"(609mm)

Grinding wheel Dimensions:Straight cup Wheel 5 7/8 × 1 1/2 × 1/2"
(150 × 38 × 13mm)Arbor Vitriified Bond

Motor Specifications:1/2H.P


Work Table Adjustment:15° to 90°

Machine Weight:80lbs(36kg)

Machine Dimensions:12High" × 24Long" × 10Deep"(305 × 609 × 254mm)


MAIN FEATURES

See Figure 1




- | | |
|---------------------------------|----------------------------------|
| 1.Table height adjustment wheel | 2.Wheel Guard/fence |
| 3.Cup grinding wheel | 4.Work Plate-adjustable(15-90°) |
| 5.Rugged 1/2 H.P. motor | 6.Table lock |
| 7.Knife height adjustment knobs | 8.Knife lock plate |

ACCESSORIES



SHARPENING DRILL BITS



SHARPENING CHISELS

BENCH MOUNT GRINDER

Place the grinder on a bench of standard height ,1"-2"(25-50mm)from the front edge of the bench.

MOUNT PIVOT PLATE

Slide the right and left lock bars (# 8 & 9) of the pivot plate assembly (item8-15) onto the table and tighten the locking knob(#10).

MOUNT WORK PLATE

Firmly mount the work plate (#7) to the pivot plate (#14) using the hardware provided (#15 or 45). Place the knife support assembly (#1-6) onto the work plate. Locate the other remaining loose items (dressing tool and the two each tool clamps) and store in a safe place.

DRESSING THE GRINDING WHEEL

After a period usage , the grinding wheel surface will become loaded and need to be dressed.

To dress the wheel follow the steps outlined below.

- 1.Loosen the table lock.
- 2.Turn the table height handwheel counterclockwise and raise the table to its highest point.
- 3.Place the dressing tool against the fence and lower the table until the diamond dresser just touches the surface of the grinding wheel.
- 4.Turn on the grinder and dress all the way across the wheel.

Repeat step 4 and 5 until the wheel is completely dressed.

NOTE : The shank of the dresser will not allow the wheel to be completely dressed across its face.There will be a ridge left on the inside edge of the grinding wheel.

CHANGE GRINDING WHEELS

Loosen and remove the fence using a 5/32"(4mm) allen wrench.


Loosen and remove the grinding wheel flange using a 5/32"(4mm) allen wrench.

Remove grinding wheel, replace with new wheel. Remount flange and socket cap screw and tighten with a 5/32"(4mm) allen wrench.

ADJUST THE KNIFE TO THE CORRECT RELIEF & INCLUDED ANGLE

On most tools it is easy to determine the correct relief and included angle. However on planer and jointer knives there is a wide range of "correct" relief and included angles. The included angle on a planer knife can vary from 30° to 60°. The woodworker is faced with hundred of varieties of woods, different moisture content and hundreds of molding and planing applications. All these factors can alter the relief and included angles found on planer and jointer knives.

With such a wide variety of accepted angles, it would not be wise to change the included angle to a predetermined setting. The best thing to do is match to the existing included angle already on the knife. Mark the beveled edge of the knife with a red marker. As a starting point rotate the pivot plate knob until the knife is held at a 30° angle. Rotate the grinding wheel handwheel until the wheel just touches the knife. With the motor off turn the grinding wheel by hand against the knife surface adjust the pivot plate until the grinding wheel will leave marks all the way across the knife edge.



MOUNTING JOINTER/PLANER KNIVES


1. Remove the knife lock top plate. place the dressing tool guide along the front edge of the knife support plate.

Adjust the height adjustment knobs until each height adjustment screw just touch the dressing tool guide.

2. Place the knife (beveled edge down) onto the knife support, firmly against the height adjustment screws.


Place the knife lock plate onto the knife support and firmly tighten the locking knobs.

NOTE: The knife must be firmly mounted against the height adjustment screws, double check at this time.




SHARPEN JOINTER/PLANER KNIVES GRINDING THE KNIFE

When facing the machine traverses the knife support assembly from the right to the left. Continue to make passes until the knife is sharp and all nicks are removed.




SHARPENING PLANER BLADES


Remove the knife support assembly and place the 2 each tool clamps onto the work plate. The tool clamps have different angles on each side of the clamp, adjust and experiment with the tool clamps until you have the best supporting angle, then turn on the motor and slide the planer blade down between the clamps and lightly sharpen the edge. Complete the sharpening in short light grinding strokes to keep the edge cool.



SHARPENING CHISELS

Chisels are sharpened in the same manner as planer blades. Adjust the tool clamps until you have the best supporting angle and sharpen and hone the edge as described in the preceding planer blade paragraphs.





DIA.
NO.

PART NAME

1	Knob
2	Knife Lock Plate
3	Knife Support
4	O-Ring
5	Hex Jam Nut 1/4-20 NC
6	Knob
7	Work Plate
8	Right Lock Bar
9	Left Lock Bar
10	Knob
11	Pivot Knob
12	Plain Washer 1/4
13	Pivot Rotate Knob
14	Pivot Plate
15	Hex Cap Screw 5/16-18 NC x 1/2 Long
16	Knob (Tool Clamp)
17	Tool Clamp
18	Lock Nut
19	Dressing Tool Guide
20	Socket Set Screw 5/16-18 NC x 3/8 Long
21	Motor Cord
22	Switch
23	Cover Plate
24	Rubber Support Feet
25	Washer
26	Phillips Round Head 10-24 x 1/2 Long
27	Capacitor
28	Motor Housing Assembly
29	Inner Flange
30	6" Grinding Wheel
31	Outer Flange
32	Socket Cap Screw
33	Hex Nut
34	Table Lock
35	Table Adjust Screw
36	Steel Balls
37	Handwheel
38	Hex Cap Screw
39	Socket Cap Screw
40	Wheel Guard
41	Spacer
42	Motor Housing Table
43	Decal
44	Cord Clip
45	Plain Washer 5/16
46	Wire Nut



WARRANTY

CRAFTEX 1 YEAR LIMITED WARRANTY

Craftex warrants every product to be free from defects in materials and agrees to correct such defects where applicable. This warranty covers **one year** for parts and 90 days for labour (unless specified otherwise), to the original purchaser from the date of purchase but does not apply to malfunctions arising directly or indirectly from misuse, abuse, improper installation or assembly, negligence, accidents, repairs or alterations or lack of maintenance.

Proof of purchase is necessary.

All warranty claims are subject to inspection of such products or part thereof and Craftex reserves the right to inspect any returned item before a refund or replacement may be issued.

This warranty shall not apply to consumable products such as blades, bits, belts, cutters, chisels, punches etceteras.

Craftex shall in no event be liable for injuries, accidental or otherwise, death to persons or damage to property or for incidental contingent, special or consequential damages arising from the use of our products.

RETURNS, REPAIRS AND REPLACEMENTS

To return, repair, or replace a Craftex product, you must visit the appropriate Busy Bee Tools showroom or call 1-800-461-BUSY. Craftex is a brand of equipment that is exclusive to Busy Bee Tools.

For replacement parts directly from Busy Bee Tools, for this machine, please call 1-800-461-BUSY (2879), and have your credit card and part number handy.

- All returned merchandise will be subject to a minimum charge of 15% for re-stocking and handling with the following qualifications.
- Returns must be pre-authorized by us in writing.
- We do not accept *collect* shipments.
- Items returned for warranty purposes must be insured and shipped pre-paid to the nearest warehouse
- Returns must be accompanied with a copy of your original invoice as proof of purchase. Returns must be in an un-used condition and shipped in their original packaging a letter explaining your reason for the return. Incurred shipping and handling charges are not refundable.
- Busy Bee will repair or replace the item at our discretion and subject to our inspection.
- Repaired or replaced items will be returned to you pre-paid by our choice of carriers.
- Busy Bee reserves the right to refuse reimbursement or repairs or replacement if a third party without our prior authorization has carried out repairs to the item.
- Repairs made by Busy Bee are warranted for 30 days on parts and labour.
- Any unforeseen repair charges will be reported to you for acceptance prior to making the repairs.
- The Busy Bee Parts & Service Departments are fully equipped to do repairs on all products purchased from us with the exception of some products that require the return to their authorized repair depots. A Busy Bee representative will provide you with the necessary information to have this done.
- For faster service it is advisable to contact the nearest Busy Bee location for parts availability prior to bringing your product in for repair.